

Feature

- :GB28184-2011 ;
- :TFT ;
- :USB✕ CAN✕ CAN✕RS485✕RS232✕ ;
- : CAN ✕ CAN ✕ ;
- : , ✕ ✕

Parameter

	DYJK-YKS4981
	AC220V D12V
(✕)	/ Ó 10W
	0~40Á C
	Ó 95%
	2 ✕ 200
	600mm ĩ 440mm ĩ 115mm
	ZR-RVS2 ĩ 2.5
	RS485 Ó 1500m✕CAN Ó 1500m,
	Ó 1000m()



Feature

- 7
-
- ✕
- /

Parameter

	DYJK-YKS4971C
	DC24V ^{+10%} _{-15%}
	Ó 7mA
	AC100V~300V50Ö1Hz
	AC 100V~300V(1V)
	Ó 5%
	LED
	1~200
	Power_Bus
	114mm ĩ 92mm ĩ 52mm
	35mm :-
	10 1 ~+40 1 , <95%



/

Parameter

	Э
	1È f 01
	-
	Ø

/

Feature

- ()
 -
 -
 -
- -
 -
 -

Parameter

	DYJK-YKS4976C
	DC24V ^{+10%} _{-15%}
	Ó 7mA
	AC200V~500V50Ô1Hz
	AC7A~300A50Ô1Hz
	AC200V~500V(1V ж
	AC 7A~300A(0.1A)
	Ó 5%
	LED
	1~200
	Power_Bus
	114mm ĩ 92mm ĩ 52mm
	35mm



:-10 1 ~+40 1 , :95%

/

Feature

- ()
 -
 -
 -
- -
 -
 -

Parameter

	DYJK-YKS4976CS
	DC24V ^{+10%} _{-15%}
	Ó 7mA
	AC200V~500V50Ô1Hz
	AC7A~300A50Ô1HZ
	AC200V~500V(1V)
	AC7A~300A(0.1A)
	Ó 5%
	LED
	1~200
	Power_Bus
	114mm ĩ 92mm ĩ 52mm
	35mm



:-10 1 ~+40 1 , :95%

/

Feature

- ()
 -
 -
 -
- -
 -
 -

Parameter

	DYJK-YKS4977C
	DC24V ^{+10%} _{-15%}
	Ó 7mA
	AC100V~300V50Ô1Hz
	AC7A~300A50Ô1HZ
	AC100V~300V(1V)
	AC 7A~300A(0.1A)
	Ó 5%
	LED
	1~200
	Power_Bus
	114mm ĩ 92mm ĩ 52mm
	35mm



:-10 1 ~+40 1 , :<95%

/

•

Parameter

	DYJK-YKS4977CS
	DC24V
	Ó 7mA
	AC100V~300V50Ô1Hz
	AC7A~300A50Ô1HZ
	AC100V~300V(1V)
	AC7A~300A(0.1A)
	Ó 5%
	LED
	1~200
	Power_Bus
	114mm ĩ 92mm ĩ 52mm
	35mm

:-10 1 ~+40 1 , 95%

/

Feature

- () ✕
 -
 - ✕
 - /
- -
 -

Parameter

	DYJK-YKS4978C
	DC24V ^{+10%} _{-15%}
	Ó 7mA
	AC100V~300V50Ô1Hz
	AC7A~300A50Ô1Hz
DC	DC10V~60V(0.1V)
	AC100V~300V(1V)
	AC7A~300A(1V)
DC	AC 10V~60V(0.1V)
	Ó 5%
	LED
	1~200
	Power_Bus
	114mm ĩ 92mm ĩ 52 mm
	35mm



:-10 1 ~+40 1 , :95%

